

NSF Product and Service Listings

These NSF Official Listings are current as of **Thursday, June 25, 2020** at 12:15 a.m. Eastern Time. Please [contact NSF](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:
<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=28470&Standard=061&>

NSF/ANSI/CAN 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).

Henkel Corporation

One Henkel Way
Rocky Hill, CT 06067
United States
860-571-5100

[Visit this company's website](#)

Facility : Clearwater, FL

Joining and Sealing Materials

Trade Designation	Water Contact Size	Water Contact Temp	Water Contact Material
Adhesives Loctite UK 178A and 178B Structural Polyurethane[1] [2]	[3]	CLD 23	ADH

[1] Minimum cure time is 7 days.

[2] Formerly Macroplast UK 178A and 178B.

[3] Mix ratio is 1:1 (A:B) by volume.

Facility : Seabrook, NH

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Adhesives			
Loctite® AA H3101[1] [2] [3]	[4]	CLD 23	ADH
Loctite® SF 7649[5] [6] [7]	4.5 joints/L	C. HOT	JNG

[1] Mix ratio is 1:1 (A:B) by weight or volume.

[2] Certification does not include use with Primer 2000.

[3] Formerly Loctite Speedbonder H3101.

[4] Certified for joining pipes and fittings 4 inches and greater.

[5] Evaluated for use with Henkel Loctite's anaerobic adhesives and sealants.

[6] Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

[7] Formerly Loctite 7649 Primer N.

Facility : Cleveland, OH

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Impregnation Resins			
Loctite® IS 88C[1]	[2]	C. HOT	SLT

[1] Certified for use with metallic materials having no greater than 20% porosity.

[2] Maximum use level for residential applications is 31 sq. in./L (335 sq. in. per residence).

Sealants

Loctite® IS RESINOL RTC™[3]	[2]	C. HOT	SLT
-----------------------------	-----	--------	-----

[2] Maximum use level for residential applications is 31 sq. in./L (335 sq. in. per residence).

[3] Formerly Loctite Resinol RTC.