



NSF Product and Service Listings

These NSF Official Listings are current as of **Saturday, October 30, 2010** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://www.nsf.org/Certified/PwsComponents/Listings.asp?Company=28470&Standard=061&>

NSF/ANSI STANDARD 61

Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#).

Henkel Corporation

1001 Trout Brook Crossing
Rocky Hill, CT 06067
United States
860-571-5100

[Visit this company's website](#)

Facility : Seabrook, NH

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Adhesives			
Loctite® 7649 Primer N[1] [2]	4.5 joints/L	C. HOT	JNG

[1] Evaluated for use with Henkel Loctite's anaerobic adhesives and sealants.

[2] Only products bearing the NSF Mark are Certified.

Facility : Cleveland, OH

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Sealants			
Loctite® Resinol® 90C	[1]	C. HOT	SLT
Loctite® Resinol® RTC	[1]	C. HOT	SLT
Vibra Seal 503HV	>= 1/2"	C. HOT	SLT

[1] Maximum use level for residential applications is 31 sq. in./L (335 sq. in. per

residence). Certified for use with brass materials having no greater than 20% porosity.

Thread Compounds

Dri-Seal® 513	>= 1/2"	C. HOT	TS
Dri-Seal® 513 HV	>= 1/2"	C. HOT	TS

Protective (Barrier) Materials

Trade Designation	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
Coatings - Fittings[1] LOCTITE® Nordbak® Brushable Ceramic Gray	>= 1"	CLD 23	EPOXY

[1] Number of Coats: 1-3

Maximum Field Use Dry Film Thickness (in mils): 120 total; 40 per coat

Recoat Cure Time and Temperature: 1 hour at 25°C

Final Cure Time and Temperature: 24 hours at 25°C

Special Comments: Mix ratio of Part A:Part B is 2.75:1 by volume or 4.8:1 by weight.

Induction time is 3-5 minutes.

Coatings - Pipe[1]

LOCTITE® Nordbak® Brushable Ceramic Gray	>= 20"	CLD 23	EPOXY
--	--------	--------	-------

[1] Number of Coats: 1-3

Maximum Field Use Dry Film Thickness (in mils): 120 total; 40 per coat

Recoat Cure Time and Temperature: 1 hour at 25°C

Final Cure Time and Temperature: 24 hours at 25°C

Special Comments: Mix ratio of Part A:Part B is 2.75:1 by volume or 4.8:1 by weight.

Induction time is 3-5 minutes.

Coatings - Valve[1]

LOCTITE® Nordbak® Brushable Ceramic Gray	>= 1"	CLD 23	EPOXY
--	-------	--------	-------

[1] Number of Coats: 1-3

Maximum Field Use Dry Film Thickness (in mils): 120 total; 40 per coat

Recoat Cure Time and Temperature: 1 hour at 25°C

Final Cure Time and Temperature: 24 hours at 25°C

Special Comments: Mix ratio of Part A:Part B is 2.75:1 by volume or 4.8:1 by weight.

Induction time is 3-5 minutes.

Facility : Shandong, China

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Thread Compounds High Strength Pipe Sealant Product 581	>= 1/2"	C. HOT	TC

Facility : Jilemnice, Czech Republic

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Sealants			

Loctite 55 Pipe Sealing Cord[1]	>= 1/4"	C. HOT	SLT
Loctite 55XL	>= 1/4"	C. HOT	SLT
Tangit UNI-LOCK	>= 1/4"	C. HOT	SLT
UNI-LOCK	>= 1/4"	C. HOT	SLT

[1] Only products bearing the NSF Mark are Certified.

Thread Compounds

Loctite 55 Pipe Sealing Cord[1]	>= 1/4"	C. HOT	TC
Loctite 55XL	>= 1/4"	C. HOT	SLT
Tangit UNI-LOCK	>= 1/4"	C. HOT	TC

[1] Only products bearing the NSF Mark are Certified.

Facility : Sabana Grande, Puerto Rico

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Adhesives			
Loctite® 242 Threadlocker Adhesive[8] [9]	>= 1/2"	D. HOT	SLT
Loctite® 680 Retaining Compound[5] [8]	>= 1/2"	C. HOT	ADH

[5] Maximum use: 10 (1/2") joints per liter.

[8] Only products bearing the NSF Mark are Certified.

[9] Certified for a maximum use of 2 joints/liter.

Sealants

Loctite® 290 Threadlocker Adhesive[8] [9]	>= 1/2"	D. HOT	SLT
Loctite® 565 PST® Pipe Sealant[4] [8]	[2]	C. HOT	TS
Loctite® PST® 561 Pipe Sealant Stick[8]	[6]	D. HOT	SLT
Sprinkler System Thread Sealant[4] [8]	[2]	C. HOT	TS
Sprinkler System Weld Sealant[8] [9]	>= 1/2"	D. HOT	TS

[2] Maximum use: 50 (1/2") joints per residence (4.5 joints per liter).

[4] This product is Certified for use as a fitting and pipe sealant.

[6] Maximum of 5 joints per liter.

[8] Only products bearing the NSF Mark are Certified.

[9] Certified for a maximum use of 2 joints/liter.

Thread Compounds

Hunting Interlock Seallube™ Tubular Thread Sealant - Field End	>= 1/2"	C. HOT	TC
Hunting Interlock Seallube™ Tubular Thread Sealant - Mill End	>= 1/2"	C. HOT	TC
Loctite® 480 Instant Adhesive[8]	>= 1/2"	C. HOT	SLT
Loctite® 518 Flange Sealant[3] [8]	>= 1/2"	C. HOT	SLT
Loctite® Threadlocker Adhesive 243[3] [8]	>= 1/2"	C. HOT	TS
Seallube HTM-1001	>= 1/2"	C. HOT	TC
Seallube LTF - 4444	>= 1/2"	C. HOT	TC
Stainless Steel PST® 567[8]	[7]	C. HOT	TC

[3] Maximum of 21 joints per residence (2 joints per liter).

[7] Certified for use as an anode thread sealant in water heater tanks with a maximum surface area to volume ratio of 0.08 sq. in./L.

[8] Only products bearing the NSF Mark are Certified.

Number of matching Manufacturers is 1

Number of matching Products is 32

Processing time was 0 seconds

- [Search Listings](#) |
- [News Room](#) |
- [About NSF](#) |
- [Careers](#) |
- [NSF Mark](#) |
- [Client Log-In](#)

- [Privacy Policy](#) |
- [Site Map](#) |
- [Request Info](#) |
- [Contact Us](#) |
- [Copyright © 2004 NSF International.](#)